

In the claims:

For the Examiner's convenience, all pending claims are presented below with changes shown in accordance with the mandatory amendment format. Please cancel claims, 19, 23, 28 and 32 without prejudice

1-19 (Canceled)

20. (Currently Amended) The system of claim 24 ~~19~~ wherein said striping controller causes data being transmitted between said interface and said first and second drives to be written to and read from the first and second drives in an interleaved form and substantially in parallel.

21. (Currently Amended) The system of claim 24 ~~19~~ wherein the data being transmitted between the system bus and the first and second disk drives is subdivided into a plurality of sequential blocks.

22. (Previously Presented) The system of claim 21 wherein the first disk drive is accessed for every other block of data and the second disk drive is accessed for the remaining blocks.

23. (Cancelled)

24. (Currently Amended) ~~The system of claim 23 wherein a least significant bit of in the sector string of the system request is mapped to a drive select bit of the first disk drive.~~

A system comprising:

a Basic Input/Output System (BIOS) to transmit a system request that includes a sector bit string, a head bit string, a track bit string and a driver bit;

a system bus coupled to said BIOS;

an integrated drive electronics (IDE) interface coupled to said system bus that communicates directly with said BIOS via said system bus;

a striping controller coupled to said IDE interface;

a first disk drive including first IDE electronics, said striping controller coupled to said first IDE electronics; and

a second disk drive including second IDE electronics, said striping controller coupled to said second IDE electronics, said first and said second IDE electronics each having data separator electronics, data formatting electronics and head positioning electronics;

wherein the data written to and read from the first and second disk drives is interleaved by mapping bits of the system request to the first and second disk drives so that even sectors are accessed on the first disk drive and odd sectors are accessed on the second disk drive and a least significant bit of the sector string of the system request is mapped to a drive select bit of the first disk drive.

25. (Currently Amended) A method comprising:

transmitting an integrated drive electronics (IDE) request from a Basic Input/Output System (BIOS) onto a system bus, the request including a sector bit string, a head bit string, a track bit string and a driver bit;

receiving said IDE request at an IDE interface connected to said system bus, said IDE interface communicating directly with said BIOS;

transmitting said IDE request to a striping controller coupled to said IDE interface and first IDE electronics of a first disk drive and second IDE electronics of a second disk drive; and

writing to and reading from the first disk drive and the second disk drive in an interleaved form by mapping of bits of ~~a system~~ IDE request to the first and second disk drives, so that even sectors on the first drive are accessed and odd sectors on the second drive are accessed, wherein a least significant bit of the sector string of the IDE request is mapped to a drive select bit of the first disk drive.

26. (Previously Presented) The method of claim 25 further comprising receiving the IDE request at the striping controller

27. (Previously Presented) The method of claim 25 further comprising writing to and reading from the first disk drive and the second disk drive substantially in parallel.

28. (Cancelled)

29. (Currently Amended) The system of claim 33 28 wherein the data is written to and read from the first and second disk drives substantially in parallel.

30. (Currently Amended) The system of claim 33 28 wherein the control logic subdivides the data being transmitted via the system bus into a plurality of sequential blocks.

31. (Previously Presented) The controller of claim 30 wherein control logic further accesses the first disk drive for every other block of data and accesses the second disk drive for the remaining blocks.

32. (Cancelled)

33. (Currently Amended) ~~The controller of claim 32 wherein a least significant bit of the sector string of the system request is mapped to a drive select bit of the first disk drive.~~

A striping disk controller comprising:

an integrated drive electronics (IDE) interface coupled to a system bus that communicates directly with a Basic Input/ Output System (BIOS) separately coupled to said system bus; and

control logic coupled to the IDE interface and first disk electronics of a first disk drive and second disk electronics of a second disk drive, the control logic to cause data being transmitted via the system bus to be written to and read from a first disk drive and a second disk drive in an interleaved form by mapping bits of a system request to the first and second disk drives so that even sectors are accessed on the first disk drive and odd sectors are accessed on the second disk drive, the system request including a sector bit string, a head bit string, a track bit string and a driver bit, wherein a least significant bit of the sector string of the system request is mapped to a drive select bit of the first disk drive.

34. (Currently Amended) The system of claim 33 ~~28~~ wherein the control logic receives a system request intended for a single physical drive from the system bus.

35. (Currently Amended) A system comprising:

a central processing unit (CPU) that executes an operating system including a Basic Input/Output Operating System (BIOS) to transmit a system request that includes a sector bit string, a head bit string, a track bit string and a driver bit;

a system bus coupled to the CPU;

an IDE interface coupled to the system bus that communicates directly with the BIOS via the system bus;

a striping controller coupled to the IDE interface;

a first storage device, including first IDE electronics, said striping controller coupled to said first IDE electronics; and

a second storage device, including second IDE electronics, said striping controller coupled to said second IDE electronics;

the striping controller, based on a standard IDE driver instruction, causes data being received to be written to and read from the first and second storage devices in an interleaved form by mapping bits of a system request to the first and second disk drives so that even sectors are accessed on the first disk drive and odd sectors are accessed on the second disk drive wherein a least significant bit of the sector string of the system request is mapped to a drive select bit of the first disk drive.

36. (Previously Presented) The system of claim 35 wherein the data is written to and read from the first and second storage substantially in parallel.

37. (Previously Presented) The system of claim 35, wherein the striping controller comprises:

an exclusive-or (XOR) gate coupled to the IDE interface;

a first FIFO memory coupled to the XOR gate and driven by a signal from the XOR gate to access the first storage device; an

a second FIFO memory coupled to the XOR gate and driven by the signal from the XOR gate to access the second storage device.